



## Product Description

### Horizontal Pivot Band Saws

> Single-Miter Saws

>> Cyclone Series

The Cyclone A-4 makes cutting 45° miter cuts in one direction perfect for cutting small solids and shapes. With a 24" indexing bar-feed and up to 4 indexes, cutting multiple parts in longer than 24" in automatic mode is possible. A variety of options are also available.

## Standard Features

Easy View Console - All Function Control  
 18" Discharge Support  
 Vise - Adjustable Main & Feed  
 Adjustable Clamping Force  
 2 Hold Down Fixtures  
 Vertical Alignment Bar on Bar-Feed  
 Guide Arm - Manual Adjustment  
 Passive "Cut Watcher®" System  
 Variable Blade Speed w/ LED Readout  
 Carbide Blade Guides  
 Manual Blade Tension  
 Adjustable Feed Rate  
 Adjustable Cutting Pressure  
 Coolant System - Flood w/ Wash-Down Hose  
 Blade Brush  
 Broken Blade Function  
 Out-of-Stock Function  
 Safety Guards  
 220V/3PH or 440V/3PH Electrical Motor  
 Requirement - This is Not a Dual Voltage Machine  
 85 PSI, 4-6 CFM Minimum Air Requirement  
 (Equipped w/ Air Filter/Lubricator)

## Technical Specifications

<b>Rectangular Capacity</b>	0-22" W x 0-16" H
<b>Square Capacity</b>	
<b>Round Capacity</b>	
<b>Bar-feed</b>	0-24" (Stroke Air - 4 Index)
<b>Motor</b>	7.5 HP
<b>Hydraulic Motor</b>	N/A
<b>Operation Type</b>	Automatic
<b>Power Source</b>	Air
<b>Weight</b>	N/A
<b>Blade Type</b>	Bandsaw
<b>Blade Size</b>	16' 0" L x 1.25" H x .042"
<b>Cantilever</b>	
<b>Bandsaw Blade Speed</b>	N/A
<b>Bundle Cut?</b>	Yes

## Optional Features

Top Clamp - Reduced Capacity Main Vise  
 Full Width Discharge Plate  
 60° Miter Capability (Manual Cut Only)  
 Powered Blade Tension

Top Clamp - Reduced Capacity Feed Vise  
 Vise - 3rd on Feed  
 Laser Light System  
 Light Clamping Pressure

Spray Mist Lubrication  
Single-Phase Voltage

5' Idle Roller Stock Table  
10' Idle Roller Stock Table

---

**HEMSAW.COM**

**1 (888) 729-7787**