



## Product Description

### Horizontal Pivot Band Saws

#### > Single-Miter Saws

#### >> Cyclone Series

The Cyclone A-C multiple indexes with a 24" bar-feed, saves up to 99 jobs, sawing one job or multiple jobs of differing lengths and quantities in sequence. Each job includes job number, part length and quantity and can miter up to 45° in one direction cutting solids or shapes.

## Standard Features

- Easy View Console - All Function Control
- Computer Controlled Feed System
- 18" Discharge Support
- Vise - Adjustable Main & Feed
- Adjustable Clamping Force
- 2 Hold Down Fixtures
- Vertical Alignment Bar on Bar-Feed
- Guide Arm - Manual Adjustment
- Passive "Cut Watcher®" System
- Variable Blade Speed w/ LED Readout
- Carbide Blade Guides
- Manual Blade Tension
- Adjustable Feed Rate
- Adjustable Cutting Pressure
- Coolant System - Flood w/ Wash-Down Hose
- Blade Brush
- Broken Blade Function
- Out-of-Stock Function
- Safety Guards
- 220V/3PH or 440V/3PH Electrical Motor
- Requirement - This is Not a Dual Voltage Machine
- 85 PSI, 4-6 CFM Minimum Air Requirement
- (Equipped w/ Air Filter/Lubricator)

## Technical Specifications

<b>Rectangular Capacity</b>	0-22" W x 0-16" H
<b>Square Capacity</b>	
<b>Round Capacity</b>	
<b>Bar-feed</b>	0-24" (Stroke Air - Multiple Index)
<b>Motor</b>	7.5 HP
<b>Hydraulic Motor</b>	N/A
<b>Operation Type</b>	Automatic
<b>Power Source</b>	Air
<b>Weight</b>	N/A
<b>Blade Type</b>	Bandsaw
<b>Blade Size</b>	16' 0" L x 1.25" H x .042"
<b>Cantilever</b>	
<b>Bandsaw Blade Speed</b>	N/A
<b>Bundle Cut?</b>	Yes

## Optional Features

- Top Clamp - Reduced Capacity Main Vise
- Vise - 3rd on Feed
- 60° Miter Capability (Manual Cut Only)
- Laser Light System

- Top Clamp - Reduced Capacity Feed Vise
- Full Width Discharge Plate
- Light Clamping Pressure
- Air Powered Blade Tension

Spray Mist Lubrication  
5' Idle Roller Stock Table

Single-Phase Voltage  
10' Idle Roller Stock Table

---

**HEMSAW.COM**

**1 (888) 729-7787**