



Product Description

Dual Column Band Saws

> Non-Miter Dual Column Saws

>> DC22 Series

The DC22M band saw is operated using a touch screen that is mounted in a swing-away console. A full-stroking split vise that positions automatically with the powered guide arm, patented Cut Watcher[®] system, and chip auger are standard and many optional features are available.

Standard Features

- Swing-Away Control Console w/ 7" Touch Screen
- 24" Solid Discharge Table
- Full-Stroking Split Main Vise
- Adjustable Clamping Force
- Carbide Blade Guides
- Lead In/Lead Out Roller Guides
- Passive "Cut Watcher[®]" System
- Guide Arm Moves in Conjunction w/ Main Vise
- Variable Blade Speed w/ Readout on Touch Screen
- Powered Blade Tension
- Adjustable Feed Rate
- Adjustable Cutting Pressure
- Chip/Swarf Removal System - Chip Auger
- Coolant System - Flood w/ Wash-Down Hose
- Blade Brush
- Two-Hand Operation Controls
- Broken Blade Function
- Automatic Blade Idle
- Blade Change Interlock
- Safety Guards
- 220V/3PH or 440V/3PH Electrical Motor
- Requirement - This is Not a Dual Voltage Machine

Technical Specifications

Rectangular Capacity	0-22" W x 0-22" H
Square Capacity	0-22" (Square)
Round Capacity	0-22" (Diameter)
Bar-feed	N/A
Motor	10 HP
Hydraulic Motor	10 HP
Operation Type	Semi-Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	21' 0" L x 2" H x .063"
Cantilever	
Bandsaw Blade Speed	N/A
Bundle Cut?	No

Optional Features

- Top Clamp - Full Capacity Main Vise
- Vise - Outboard Powered on Discharge
- Roller Discharge Table (in Lieu of Solid)
- Pedestal Mounted Control Console
- Spray Mist Lubrication
- Hydraulic Tank Heater
- 10' Idle Roller Stock Table

- Top Clamp - Full Capacity Outboard Vise
- 36" Roller Load Table w/ Filler Plates
- Laser Light System
- Roll-Around Control Console
- Cold Weather Package
- 10' Powered Roller Stock Table
- 5' Idle Roller Stock Table

