



Product Description

Dual Column Band Saws

> Non-Miter Dual Column Saws

>> DC40+ Series

The DC4045 is operated using a touch screen control in a pedestal mounted console and can be operated in manual or semi-automatic modes. Full stroking variable-pressure vise and powered guide arm are standard along with other features. Active Cut Watcher[®] is standard and options are available

Standard Features

- Pedestal Mounted Control Console w/ 9" Touch Screen
- Industrial IOT Ready - MTConnect Output
- Servo Controlled Traverse (SCT)
- 8' Powered Base
- Vise - Full Stroking Main
- Adjustable Clamping Force
- Carbide Blade Guides
- Active "Cut Watcher[®]" System
- Guide Arm - Powered
- Variable Blade Speed w/ Readout on Touch Screen
- Powered Blade Tension
- Shadow Light System
- Coolant System - Flood w/ Wash-Down Hose
- Blade Brush
- Two-Hand Operation Controls
- Broken Blade Function
- Automatic Blade Idle
- Blade Change Interlock
- Safety Guards
- 220V/3PH or 440V/3PH Electrical Motor
- Requirement - This is Not a Dual Voltage Machine

Technical Specifications

Rectangular Capacity	0-45" W x 0-40" H
Square Capacity	0-40" (Square)
Round Capacity	0-40" (Diameter)
Bar-feed	N/A
Motor	30 HP
Hydraulic Motor	5 HP
Operation Type	Semi-Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	33' 0" L x 2.625" H x .063"
Cantilever	
Bandsaw Blade Speed	N/A
Bundle Cut?	No

Optional Features

- Chip/Swarf Removal System - Chip Conveyor
- Remote Diagnostics
- Cold Weather Package

- 3-1/8" Blade Option
- Hydraulic Tank Heater

