



## Product Description

### Horizontal Pivot Band Saws

> Non-Miter Horizontal Pivot Saws

>> H105 Series

The H105A-C includes a 24" bar-feed and allows multiple indexes and the ability to create and save up to 99 jobs. Each job includes a job number, the part length, and quantity and runs consecutive jobs in sequence.

## Standard Features

Easy View Console - All Function Control

Computer Controlled Feed System

24" Solid Discharge Table - Bolts to Saw

Vise - Adjustable Main & Feed

Adjustable Clamping Force

2 Hold Down Fixtures

Vertical Alignment Roller on Bar-Feed

Guide Arm - Manual Adjustment

Passive "Cut Watcher®" System

Variable Blade Speed w/ LED Readout

Carbide Blade Guides

Air Powered Blade Tension

Adjustable Feed Rate

Adjustable Cutting Pressure

Coolant System - Flood w/ Wash-Down Hose

Chip/Swarf Removal System - Chip Auger

Blade Brush

Broken Blade Function

Out-of-Stock Function

Safety Guards

220V/3PH or 440V/3PH Electrical Motor

Requirement - This is Not a Dual Voltage Machine

85 PSI, 4-6 CFM Minimum Air Requirement

(Equipped w/ Air Filter/Lubricator)

## Technical Specifications

<b>Rectangular Capacity</b>	0-16" W x 0-14" H
<b>Square Capacity</b>	0-14" (Square)
<b>Round Capacity</b>	0-14" (Diameter)
<b>Bar-feed</b>	0-24" (Stroke Air - Multiple Index)
<b>Motor</b>	7.5 HP
<b>Hydraulic Motor</b>	N/A
<b>Operation Type</b>	Automatic
<b>Power Source</b>	Air
<b>Weight</b>	N/A
<b>Blade Type</b>	Bandsaw
<b>Blade Size</b>	15' 0" L x 1.25" H x .042"
<b>Cantilever</b>	
<b>Bandsaw Blade Speed</b>	N/A
<b>Bundle Cut?</b>	Yes

## Optional Features

Top Clamp - Reduced Capacity Main Vise

Vise - 3rd on Feed

Vise - Outboard Powered on Discharge

Spray Mist Lubrication

Top Clamp - Reduced Capacity Feed Vise

Interlocking Vise Jaws

Light Clamping Pressure

Single-Phase Voltage

---

**HEMSAW.COM**

**1 (888) 729-7787**