



Product Description

Dual Column Band Saws

> Non-Miter Dual Column Saws

>> H130-DC Series

The H130M-DC is operated using a touch screen control mounted in a swing-away console and can be operated in manual or semi-automatic modes. Full stroking variable-pressure vise and powered guide arm are standard along with other features. Many options are available.

Standard Features

- Swing-Away Control Console w/ 7" Touch Screen
- 24" Solid Discharge Table
- Vise - Full Stroking Main
- Adjustable Clamping Force
- Carbide Blade Guides
- Lead In/Lead Out Roller Guides
- Guide Arm - Powered
- Powered Blade Tension
- Variable Blade Speed w/ Readout on Touch Screen
- Adjustable Feed Rate
- Adjustable Cutting Pressure
- Coolant System - Flood w/ Wash-Down Hose
- Blade Brush
- Broken Blade Function
- Safety Guards
- 220V/3PH or 440V/3PH Electrical Motor
- Requirement - This is Not a Dual Voltage Machine

Technical Specifications

Rectangular Capacity	0-20" W x 0-20" H
Square Capacity	0-20" (Square)
Round Capacity	0-20" (Diameter)
Bar-feed	N/A
Motor	10 HP
Hydraulic Motor	2 HP
Operation Type	Semi-Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	19' 0" L x 1.5" H x .050"
Cantilever	
Bandsaw Blade Speed	N/A
Bundle Cut?	No

Optional Features

- Top Clamp - Full Capacity Main Vise
- Vise - Outboard Powered on Discharge
- Passive "Cut Watcher[®]" System
- Pedestal Mounted Control Console
- Hydraulic Tank Heater
- Spray Mist Lubrication
- 5' Discharge Table Extension

- Top Clamp - Full Capacity Outboard Vise
- Chip/Swarf Removal System - Chip Auger
- Laser Light System
- Roll-Around Control Console
- Cold Weather Package
- 10' Powered Roller Load Table
- 10' Discharge Table Extension

10' Powered Discharge Table Extension
10' Idle Roller Stock Table

5' Idle Roller Stock Table
10' Powered Roller Stock Table

HEMSAW.COM

1 (888) 729-7787