



Product Description

Dual Column Band Saws

> Non-Miter Dual Column Saws

>> H3236-DC Series

The H3236M-DC is operated using a touch screen control mounted in a swing-away console and can be operated in manual or semi-automatic modes. Full stroking variable-pressure vise and powered guide arm are standard along with other features. Many options are available.

Standard Features

Swing-Away Control Console w/ 7" Touch Screen
 24" Roller Discharge Table
 Vise - Full Stroking Main
 Adjustable Clamping Force
 Carbide Blade Guides
 Lead In/Lead Out Roller Guides
 Passive "Cut Watcher®" System
 Guide Arm - Powered
 Variable Blade Speed w/ Readout on Touch Screen
 Adjustable Feed Rate
 Adjustable Cutting Pressure
 Powered Blade Tension
 Coolant System - Flood w/ Wash-Down Hose
 Blade Brush
 Broken Blade Function
 Two-Hand Operation Controls
 Automatic Blade Idle
 Safety Guards
 Blade Change Interlock
 220V/3PH or 440V/3PH Electrical Motor
 Requirement - This is Not a Dual Voltage Machine

Technical Specifications

Rectangular Capacity	0-36" W x 0-32" H
Square Capacity	0-32" (Square)
Round Capacity	0-32" (Diameter)
Bar-feed	N/A
Motor	20 HP
Hydraulic Motor	5 HP
Operation Type	Semi-Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	27' 0" L x 2" H x .063"
Cantilever	
Bandsaw Blade Speed	N/A
Bundle Cut?	No

Optional Features

Top Clamp - Full Capacity Main Vise
 Vise - Outboard Powered on Discharge
 Chip/Swarf Removal System - Chip Conveyor
 Shadow Light System
 Pedestal Mounted Control Console
 Cold Weather Package
 10' Idle Roller Load Table

Top Clamp - Full Capacity Outboard Vise
 2-5/8" Blade Option - HD Gear Box
 Laser Light System
 Spray Mist Lubrication
 Roll-Around Control Console
 Hydraulic Tank Heater
 10' Powered Roller Load Table

5' Discharge Table Extension
10' Powered Discharge Table Extension
10' Idle Roller Stock Table

10' Discharge Table Extension
5' Idle Roller Stock Table
10' Powered Roller Stock Table

HEMSAW.COM

1 (888) 729-7787