





## **Technical Specifications**

Rectangular Capacity

**Square Capacity** 1.575-4.33" (Square)

**Round Capacity** 1.575-6.023" (Diameter)

Bar-feed N/A

Motor 25 HP

**Hydraulic Motor** 5 HP

**Operation Type** Automatic

**Power Source** Hydraulic

Weight N/A

**Blade Type** Circular

**Primary Circular** TCT Carbide Tipped---360mm

Blade Diameter --- [75-600 RPM]

**Optional Circular** TCT Carbide Tipped---460mm

**Blade** (1) Diameter --- [100-760 RPM]

**Bundle Cut?** No

## **Product Description**

Circular Saws
> CNC Steel Saws

The KTC-150SP carbide sawing machine is controlled with a touch screen interface. The saw head is driven by a servo motor and the hydraulics are hard-plumbed for more consistent operation. An automatic work piece loader for handling and positioning material before the cut is standard. Options are available.

## **Standard Features**

Uses TCT Carbide Tipped Saw Blade 360 x 2.26t

mm x 460 x 2.7t mm

Option to Use HSS High-Speed Steel Saw Blade

460 x 3.0t-5.0t mm Blade Feed Slope Type

Compact PLC Control & Inverter

Touch Screen Feature for Setting Machine & Cut

**Functions** 

Saw Blade Feed Driven by Servo Motor

Hard-Plumbed Hydraulic System

Vise - Hydraulic Horizontal & Vertical Main Stroking Front "Outboard" Vise (Reduces

Remnant Lengths)

20' Standard Loader - Automatic Workpiece

Loading

Automatic Product Sorting Work Piece Positioning

Precision Spindle

Variable Blade Speed

Magnetic Power Brake and Fan

Blade Brush

Chip Removal - Air Gun & Belt Type Chip

Conveyor

Built-In Coolant System w/ Flood & Mist

208-240V, 50/60hz, 3-Phase

## **Optional Features**

10' Standard Loader Extention (up to 60' total) 10' Bundle Loader Extention (up to 60' total) Sliding Aid 20' Bundle Loader Unloading Device Mist Collection System