



## Product Description

### Horizontal Pivot Band Saws

> Single-Miter Saws

>> Sidewinder Series

The Sidewinder A-4 cuts 45° miters in one direction and is perfect for cutting small solids and shapes. With a 24" indexing bar-feed and up to 4 indexes, cutting multiple parts in longer than 24" in automatic mode is possible. A variety of options are also available.

## Standard Features

Easy View Console - All Function Control

18" Discharge Support

Vise - Adjustable Main & Feed

Adjustable Clamping Force

2 Hold Down Fixtures

Vertical Alignment Bar on Bar-Feed

Guide Arm - Manual Adjustment

Passive "Cut Watcher®" System

Variable Blade Speed w/ LED Readout

Carbide Blade Guides

Manual Blade Tension

Adjustable Feed Rate

Adjustable Cutting Pressure

Coolant System - Flood w/ Wash-Down Hose

Blade Brush

Broken Blade Function

Out-of-Stock Function

Safety Guards

220V/3PH or 440V/3PH Electrical Motor

Requirement - This is Not a Dual Voltage Machine

85 PSI, 4-6 CFM Minimum Air Requirement

(Equipped w/ Air Filter/Lubricator)

## Technical Specifications

<b>Rectangular Capacity</b>	0-16" W x 0-12.75" H
<b>Square Capacity</b>	0-12.75" (Square)
<b>Round Capacity</b>	0-12.75" (Diameter)
<b>Bar-feed</b>	0-24" (Stroke Air - 4 Index)
<b>Motor</b>	3 HP
<b>Hydraulic Motor</b>	N/A
<b>Operation Type</b>	Automatic
<b>Power Source</b>	Air
<b>Weight</b>	N/A
<b>Blade Type</b>	Bandsaw
<b>Blade Size</b>	13' 6" L x 1" H x .035"
<b>Cantilever</b>	
<b>Bandsaw Blade Speed</b>	N/A
<b>Bundle Cut?</b>	Yes

## Optional Features

Top Clamp - Reduced Capacity Main Vise

Vise - 3rd on Feed

Full Width Discharge Plate

Pedestal Mounted Control Console

Top Clamp - Reduced Capacity Feed Vise

60° Miter Capability (Manual Cut Only)

Laser Light System

Light Clamping Pressure

Spray Mist Lubrication  
5' Roller Stock Table

Single-Phase Voltage  
10' Idle Roller Stock Table

---

**HEMSAW.COM**

**1 (888) 729-7787**