



Product Description

Vertical Band Saws

> Vertical Double-Miter Saws

>> V/VT140 Series

The V140 and VT140HM-60-CTS band saws vary from a vertical blade orientation on the V140 to a forward-canting blade on the VT140 version. The touch screen control, mounted in a swing-away console, allows the operator to enter an angle and the arm will travel to that position and stop.

Standard Features

Swing-Away Control Console w/ 7" Touch Screen
 Powered Programmable Tilt w/ Angle Readout
 Vise - Full Stroking Main
 Adjustable Clamping Force
 Carbide Blade Guides
 Guide Arm - Powered
 Variable Blade Speed w/ Readout on Touch Screen
 Electronic Controlled Traverse (Controls Feed Rate & Cutting Force)
 Idle Base Rollers - 1 Each Side of Base
 Powered Blade Tension
 Forward Cut Stop
 Coolant System - Flood w/ Wash-Down Hose
 Blade Brush
 Broken Blade Function
 Blade Change Interlock
 Safety Guards
 220V/3PH or 440V/3PH Electrical Motor
 Requirement - This is Not a Dual Voltage Machine

Technical Specifications

Rectangular Capacity	0-24" W x 0-31" H
Square Capacity	0-24" (Square)
Round Capacity	0-24" (Diameter)
Bar-feed	N/A
Motor	10 HP
Hydraulic Motor	5 HP
Operation Type	Semi-Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	20' 0" L x 1.5" H x .050"
Cantilever	Fixed
Bandsaw Blade Speed	N/A
Bundle Cut?	Yes

Optional Features

Swing-Away Top Clamp - Main Vise
 Vise - 2nd Main
 Laser Light System

Chip/Swarf Removal System - Chip Conveyor
 Spray Mist Lubrication
 5' Roller Load Table

Top Clamp - Reduced Capacity Main Vise
 Passive "Cut Watcher®" System
 Power Raised Lift Up Rollers
 Chip/Swarf Removal System - Manual Hand-Crank
 Chip Conveyor
 Pedestal Mounted Control Console
 10' Idle Roller Load Table

10' Powered Roller Load Table
10' Roller Discharge Table
5' Idle Roller Stock Table
10' Powered Roller Stock Table

5' Roller Discharge Table
10' Powered Roller Discharge Table
10' Idle Roller Stock Table

HEMSAW.COM

1 (888) 729-7787