



Product Description

Vertical Band Saws

> Vertical Double-Miter Saws

>> V/VT200 Series

The V200HM-CTS band saw is operated by a touch screen control that is located in a swing-away console at the front of the saw and allows the operator to enter an angle and the arm will travel to that position and stop.

Standard Features

Swing-Away Control Console w/ 7" Touch Screen
 Powered Programmable Tilt w/ Angle Readout
 Vise - Full Stroking Main & 2nd Main
 Adjustable Clamping Force
 Broken Blade Function
 Carbide Blade Guides
 Guide Arm - Powered
 Electronic Controlled Traverse (Controls Feed Rate & Cutting Force)
 Variable Blade Speed w/ Readout on Touch Screen
 Forward Cut Stop
 Power Raised Lift Up Rollers
 Powered Blade Tension
 Chip/Swarf Removal System - Chip Conveyor
 Coolant System - Flood w/ Wash-Down Hose
 Blade Brush
 Blade Change Interlock
 Safety Guards
 220V/3PH or 440V/3PH Electrical Motor
 Requirement - This is Not a Dual Voltage Machine

Technical Specifications

Rectangular Capacity	0-25" W x 0-36" H
Square Capacity	0-25" (Square)
Round Capacity	0-25" (Diameter)
Bar-feed	N/A
Motor	15 HP
Hydraulic Motor	5 HP
Operation Type	Semi-Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	20' 6" L x 2" H x .063"
Cantilever	
Bandsaw Blade Speed	N/A
Bundle Cut?	Yes

Optional Features

Swing-Away Top Clamp - Main Vise
 Passive "Cut Watcher®" System
 Roll-Around Control Console
 Spray Mist Lubrication
 10' Idle Roller Load Table
 10' Roller Discharge Table

Laser Light System
 Pedestal Mounted Control Console
 Right to Left Feed Direction
 5' Roller Load Table
 5' Roller Discharge Table

