



Product Description

Vertical Band Saws

> Vertical Double-Miter Saws

>> V/VT100 Series

The VT100HLM-60-CTS mitters up to 60° in both directions. The control console is located in a swing-away console at the front of the saw. A touch screen is used to operate the various functions on the saw. Optional vises and other features are available.

Standard Features

Swing-Away Control Console w/ 7" Touch Screen
 4° Removable Arm Cant
 Powered Programmable Tilt w/ Angle Readout
 Vise - Full Stroking Main
 Adjustable Clamping Force
 Carbide Blade Guides
 Guide Arm - Powered
 Variable Blade Speed w/ Readout on Touch Screen
 Electronic Controlled Traverse (Controls Feed Rate & Cutting Force)
 Powered Blade Tension
 Forward Cut Stop
 Coolant System - Flood w/ Wash-Down Hose
 Boltable Side Wings for Coolant Drainage
 Blade Brush
 Broken Blade Function
 Safety Guards
 220V/3PH or 440V/3PH Electrical Motor
 Requirement - This is Not a Dual Voltage Machine

Technical Specifications

Rectangular Capacity	0-18" W x 0-20.75" H
Square Capacity	0-18" (Square)
Round Capacity	0-18" (Diameter)
Bar-feed	N/A
Motor	5 HP
Hydraulic Motor	2 HP
Operation Type	Semi-Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	15' 6" L x 1.25" H x .042"
Cantilever	Removable
Bandsaw Blade Speed	N/A
Bundle Cut?	Yes

Optional Features

Swing-Away Top Clamp - Main Vise
 Vise - 2nd Main
 Power Raised Lift Up Rollers
 Laser Light System
 Spray Mist Lubrication
 10' Idle Roller Load Table
 10' Roller Discharge Table

Top Clamp - Reduced Capacity Main Vise
 Passive "Cut Watcher®" System
 12" H Wear Plates - Non Mitered
 Pedestal Mounted Control Console
 5' Roller Load Table
 5' Roller Discharge Table
 5' Idle Roller Stock Table

HEMSAW.COM

1 (888) 729-7787