



Product Description

Vertical Band Saws

> Vertical Double-Miter Saws

>> V/VT120 Series

The VT120HM-60-CTS miteres up to 60° in both directions. The control console is located in a swing-away console at the front of the saw. A touch screen is used to operate the various functions on the saw. Optional vises and other features are available.

Standard Features

Swing-Away Control Console w/ 7" Touch Screen
 Powered Programmable Tilt w/ Angle Readout
 Vise - Full Stroking Main
 Adjustable Clamping Force
 Variable Blade Speed w/ Readout on Touch Screen
 Carbide Blade Guides
 Guide Arm - Powered
 Electronic Controlled Traverse (Controls Feed Rate & Cutting Force)
 Powered Blade Tension
 Idle Base Rollers - 1 Each Side of Base
 Forward Cut Stop
 Coolant System - Flood w/ Wash-Down Hose
 Blade Brush
 Broken Blade Function
 Safety Guards
 220V/3PH or 440V/3PH Electrical Motor
 Requirement - This is Not a Dual Voltage Machine

Technical Specifications

Rectangular Capacity	0-18" W x 0-24" H
Square Capacity	0-18" (Square)
Round Capacity	0-18" (Diameter)
Bar-feed	N/A
Motor	7.5 HP
Hydraulic Motor	5 HP
Operation Type	Semi-Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	16' 6" L x 1.25" H x .042"
Cantilever	Fixed
Bandsaw Blade Speed	N/A
Bundle Cut?	Yes

Optional Features

Vise - 2nd Main
 Top Clamp - Reduced Capacity Main Vise
 Laser Light System
 Power Raised Lift Up Rollers
 Spray Mist Lubrication
 Cold Weather Package

Swing-Away Top Clamp - Main Vise
 Passive "Cut Watcher®" System
 Chip/Swarf Removal System - Manual Hand-Crank
 Chip Conveyor
 Powered Chip Conveyor
 Pedestal Mounted Control Console
 Hydraulic Tank Heater

5' Roller Load Table
5' Roller Discharge Table
10' Powered Roller Discharge Table
10' Idle Roller Stock Table

10' Powered Roller Load Table
10' Roller Discharge Table
5' Idle Roller Stock Table

HEMSAW.COM

1 (888) 729-7787