



Product Description

Vertical Band Saws
 > **Vertical Double-Miter Saws**
 >> **V/VT200 Series**

The VT200HA-60-CTS band saw is operated using a touch screen control that includes a material list and allows saving jobs for future use. A touch screen control operates the functions and the programmable arm can miter up to 60° in both directions.

Technical Specifications

Rectangular Capacity	0-25" W x 0-36" H
Square Capacity	0-25" (Square)
Round Capacity	0-25" (Diameter)
Bar-feed	0-48" (Stroke Servo Twin Ball-Screw - Multiple Index)
Motor	15 HP
Hydraulic Motor	5 HP
Operation Type	Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	24' 8" L x 2" H x .063"
Cantilever	Fixed
Bandsaw Blade Speed	N/A
Bundle Cut?	Yes

Standard Features

Swing-Away Control Console w/ 8" Touch Screen
 Computer Controlled Feed System
 Powered Programmable Tilt w/ Angle Readout
 Vises - Full Stroking Including 2nd Main Vise
 Adjustable Clamping Force
 Electronic Controlled Traverse (Controls Feed Rate & Cutting Force)
 Carbide Blade Guides
 Passive "Cut Watcher®" System
 Forward Cut Stop
 Power Raised Lift Up Rollers
 Powered Blade Tension
 Guide Arm - Powered
 Variable Blade Speed w/ Readout on Touch Screen
 Chip/Swarf Removal System - Chip Conveyor
 Coolant System - Flood w/ Wash-Down Hose
 Blade Saver
 Two-Hand Operation Controls
 Blade Brush
 Broken Blade Function
 Out-of-Stock Function
 Blade Change Interlock
 Safety Guards
 220V/3PH or 440V/3PH Electrical Motor
 Requirement - This is Not a Dual Voltage Machine

Optional Features

0-120" Stroke Servo Twin Ball-Screw Bar-Feed w/ 3rd Vise
 Swing-Away Top Clamp - Main Vise
 Vise - 3rd on Feed
 Right to Left Feed Direction

Bar-Feed Filler Plates
 Top Clamp - Full Capacity Feed Vise
 Laser Light System
 Spray Mist Lubrication

Pedestal Mounted Control Console
Hydraulic Tank Heater
10' Roller Discharge Table

Cold Weather Package
5' Roller Discharge Table

HEMSAW.COM

1 (888) 729-7787