



Product Description

Vertical Band Saws

> Vertical Double-Miter Saws

>> V/VT200 Series

The VT200HM-CTS band saw is operated by a touch screen control that is located in a swing-away console at the front of the saw and allows the operator to enter an angle and the arm will travel to that position and stop. The arm has a forward cant.

Standard Features

- Swing-Away Control Console w/ 7" Touch Screen
- Powered Programmable Tilt w/ Angle Readout
- Vise - Full Stroking Main & 2nd Main
- Adjustable Clamping Force
- Carbide Blade Guides
- Guide Arm - Powered
- Electronic Controlled Traverse (Controls Feed Rate & Cutting Force)
- Variable Blade Speed w/ Readout on Touch Screen
- Forward Cut Stop
- Powered Blade Tension
- Chip/Swarf Removal System - Chip Conveyor
- Power Raised Lift Up Rollers
- Coolant System - Flood w/ Wash-Down Hose
- Blade Brush
- Broken Blade Function
- Blade Change Interlock
- Safety Guards
- 220V/3PH or 440V/3PH Electrical Motor
- Requirement - This is Not a Dual Voltage Machine

Technical Specifications

Rectangular Capacity	0-25" W x 0-36" H
Square Capacity	0-25" (Square)
Round Capacity	0-25" (Diameter)
Bar-feed	N/A
Motor	15 HP
Hydraulic Motor	5 HP
Operation Type	Semi-Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	24' 8" L x 2" H x .063"
Cantilever	Fixed
Bandsaw Blade Speed	N/A
Bundle Cut?	Yes

Optional Features

- Swing-Away Top Clamp - Main Vise
- Passive "Cut Watcher[®]" System
- Pedestal Mounted Control Console
- Hydraulic Tank Heater
- 10' Roller Discharge Table
- 10' Powered Roller Stock Table

- Laser Light System
- Spray Mist Lubrication
- Cold Weather Package
- 5' Roller Discharge Table
- 5' Roller Load Table

