



Product Description

Dual Column Band Saws

> Wide Flange/Bundle Saws

>> WF190 Series

The WF190M band saw is designed to cut structural shapes and bundles efficiently using a fixed 9.2° canted blade. Operated with a touch-screen control mounted in a swing-away console it includes a full-stroking bi-directional main vise. Many options are available including additional top clamps and outboard vise.

Technical Specifications

Rectangular Capacity	0-44" W x 0-25" H
Square Capacity	0-25" (Square)
Round Capacity	0-25" (Diameter)
Bar-feed	N/A
Motor	15 HP
Hydraulic Motor	5 HP
Operation Type	Semi-Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	29' 0" L x 2" H x .063"
Cantilever	
Bandsaw Blade Speed	N/A
Bundle Cut?	Yes

Standard Features

Swing-Away Control Console w/ 7" Touch Screen
Arm Cant - 9.2° Permanent
24" Roller Discharge Table
Vise - Full Stroking Bi-Directional Main
Adjustable Clamping Force
Carbide Blade Guides
Lead In/Lead Out Roller Guides
Guide Arm - Powered
Adjustable Feed Rate
Adjustable Cutting Pressure
Variable Blade Speed w/ Readout on Touch Screen
Powered Blade Tension
Coolant System - Flood w/ Wash-Down Hose
Blade Brush
Two-Hand Operation Controls
Broken Blade Function
Automatic Blade Idle
Blade Change Interlock
Safety Guards
220V/3PH or 440V/3PH Electrical Motor
Requirement - This is Not a Dual Voltage Machine

Optional Features

Top Clamp - Full Capacity Main Vise
Vise - Bi-Directional Outboard
Chip/Swarf Removal System - Chip Conveyor
Laser Light System
Cold Weather Package
Roll-Around Control Console
10' Idle Roller Load Table

Top Clamp - Full Capacity Outboard Vise
2-5/8" Blade Option - HD Gear Box
Passive "Cut Watcher®" System
Spray Mist Lubrication
Pedestal Mounted Control Console
Hydraulic Tank Heater
5' Discharge Table Extension

10' Powered Discharge Table Extension
10' Idle Roller Stock Table

5' Idle Roller Stock Table
10' Powered Roller Stock Table

HEMSAW.COM

1 (888) 729-7787