



## Product Description

### Dual Column Band Saws

#### > Dual Column Double-Miter Saws

The WF190MRB-DC is a powered double-miter band saw operated using a touch screen mounted in a pedestal control console and cuts miter angles 45° in one direction and up to 60° the other direction. Included are vises on both sides of the blade with additional clamping optional.

## Standard Features

- Pedestal Mounted Control Console w/ 7" Touch Screen
- Rotary Base Machine
- Powered Miter w/ Angle Readout
- Arm Cant - 7° Permanent
- Vises on Both Sides of the Blade
- Adjustable Clamping Force
- Adjustable Feed Rate
- Adjustable Cutting Pressure
- Carbide Blade Guides
- Lead In/Lead Out Roller Guides
- Guide Arm - Powered
- Variable Blade Speed w/ Readout on Touch Screen
- Powered Blade Tension
- Coolant System - Flood w/ Wash-Down Hose
- Blade Brush
- Two-Hand Operation Controls
- Automatic Blade Idle
- Broken Blade Function
- Blade Change Interlock
- Safety Guards
- 220V/3PH or 440V/3PH Electrical Motor
- Requirement - This is Not a Dual Voltage Machine

## Technical Specifications

<b>Rectangular Capacity</b>	0-44" W x 0-25" H
<b>Square Capacity</b>	0-25" (Square)
<b>Round Capacity</b>	0-25" (Diameter)
<b>Bar-feed</b>	N/A
<b>Motor</b>	15 HP
<b>Hydraulic Motor</b>	5 HP
<b>Operation Type</b>	Semi-Automatic
<b>Power Source</b>	Hydraulic
<b>Weight</b>	N/A
<b>Blade Type</b>	Bandsaw
<b>Blade Size</b>	31' 4" L x 2" H x .063"
<b>Cantilever</b>	
<b>Bandsaw Blade Speed</b>	N/A
<b>Bundle Cut?</b>	Yes

## Optional Features

- Telescoping Roller Table - Input Side
- Top Clamp (Available Input & Output Sides)
- Passive "Cut Watcher®" System
- Laser Light System
- Cold Weather Package

- Telescoping Roller Table - Output Side
- Positioning Vise
- Chip/Swarf Removal System - Chip Conveyor
- Spray Mist Lubrication
- Hydraulic Tank Heater