

WF190MRB



Technical Specifications

Rectangular Capacity	0-44" W x 0-25" H
Square Capacity	0-25" (Square)
Round Capacity	0-25" (Diameter)
Bar-feed	N/A
Motor	15 HP
Hydraulic Motor	5 HP
Operation Type	Semi-Automatic
Power Source	Hydraulic
Weight	N/A
Blade Type	Bandsaw
Blade Size	31' 4" L x 2" H x .063"
Cantilever	
Bandsaw Blade Speed	N/A
Bundle Cut?	Yes

Product Description

Dual Column Band Saws

> Dual Column Double-Miter Saws

The WF190MRB-DC is a powered double-miter band saw operated using a touch screen mounted in a pedestal control console and cuts miter angles 45? in one direction and up to 60? the other direction. Included are vises on both sides of the blade with additional clamping optional.

Standard Features

Pedestal Mounted Control Console w/ 7" Touch Screen **Rotary Base Machine** Powered Miter w/ Angle Readout Arm Cant - 7° Permanent Vises on Both Sides of the Blade Adjustable Clamping Force Adjustable Feed Rate Adjustable Cutting Pressure Carbide Blade Guides Lead In/Lead Out Roller Guides Guide Arm - Powered Variable Blade Speed w/ Readout on Touch Screen Powered Blade Tension Coolant System - Flood w/ Wash-Down Hose Blade Brush **Two-Hand Operation Controls** Automatic Blade Idle **Broken Blade Function** Blade Change Interlock Safety Guards 220V/3PH or 440V/3PH Electrical Motor Requirement - This is Not a Dual Voltage Machine

Optional Features

Telescoping Roller Table - Input Side Top Clamp (Available Input & Output Sides) Passive "Cut Watcher®" System Laser Light System Cold Weather Package Telescoping Roller Table - Output Side Positioning Vise Chip/Swarf Removal System - Chip Conveyor Spray Mist Lubrication Hydraulic Tank Heater

HEMSAW.COM

1 (888) 729-7787